

ABB string inverters

PVI-10.0/12.5-TL-OUTD

10 to 12.5 kW



Designed for commercial usage, this PVI-10/12.5, three-phase inverter is highly unique in its ability to control the performance of the PV panels, especially during periods of variable weather conditions.

The high speed and precise Maximum Power Point Tracking (MPPT) algorithm provides real-time power tracking and improved energy harvesting.

Two independent MPPTs and efficiency ratings up to 97.8%

This transformerless device has two independent MPPTs and efficiency ratings of up to 97.8%.

Flat efficiency curves ensure high efficiency at all output levels ensuring consistent and stable performance across the entire input voltage and output power range.

The wide input voltage range makes the inverter suitable for low power installations with reduced string size.

Highlights

- True three-phase bridge topology for DC/AC output converter
- Transformerless topology
- Each inverter is set on specific grid codes which can be selected in the field
- Wide input voltage range
- Dual input section with independent MPPT allows optimal energy harvesting from two sub-arrays oriented in different directions

Additional highlights


- ‘Electrolyte-free’ power converter to further increase the life expectancy and long term reliability
- Integrated DC disconnect switch in compliance with international standards (-S and -FS versions)
- Natural convection cooling for maximum reliability
- Outdoor enclosure for unrestricted use under any environmental conditions
- RS-485 communication interface (for connection to laptop or data logger)



Technical data and types

Type code	PVI-10.0-TL-OUTD		PVI-12.5-TL-OUTD
Input side			
Absolute maximum DC input voltage (V _{max,abs})	900 V		
Start-up DC input voltage (V _{start})	360 V (adj. 250...500 V)		
Operating DC input voltage range (V _{dcmín...V_{dcmáx}})	0.7 x V _{start} ...850 V (min 200 V)		
Rated DC input voltage (V _{dcr})	580 V		
Rated DC input power (P _{dcr})	10300 W	12800 W	
Number of independent MPPT	2		
Maximum DC input power for each MPPT (P _{MPPTmax})	6500 W	8000 W	
DC input voltage range with parallel configuration of MPPT at P _{acr}	300...750 V	360...750 V	
DC power limitation with parallel configuration of MPPT	Linear derating from max to null [750 V≤V _{MPPT} ≤850 V]		
DC power limitation for each MPPT with independent configuration of MPPT at P _{acr} , max unbalance example	6500 W [380 V≤V _{MPPT} ≤750 V] the other channel: P _{dcr} -6500 W [225 V≤V _{MPPT} ≤750 V]	8000 W [445 V≤V _{MPPT} ≤750 V] the other channel: P _{dcr} -8000 W [270 V≤V _{MPPT} ≤750 V]	
Maximum DC input current (I _{dcmáx}) / for each MPPT (I _{MPPTmax})	34.0 A / 17.0 A	36.0 A / 18.0 A	
Maximum input short circuit current for each MPPT	22.0 A		
Number of DC inputs pairs for each MPPT	2 (-S version) 3 (Standard or -FS version)		
DC connection type	Tool Free PV connector WM / MC4		
Input protection			
Reverse polarity protection	Inverter protection only, from limited current source, for standard and -S versions, and for -FS version when max 2 strings are connected		
Input over voltage protection for each MPPT - varistor	Yes		
Photovoltaic array isolation control	According to local standard		
DC switch rating for each MPPT (version with DC switch)	25 A / 1000 V		
Fuse rating (versions with fuses)	12 A / 1000 V		
Output side			
AC grid connection type	Three-phase 3W+PE or 4W+PE		
Rated AC power (P _{acr} @cosφ=1)	10000 W	12500 W	
Maximum AC output power (P _{acmax} @cosφ=1)	11000 W ³⁾	13800 W ⁴⁾	
Maximum apparent power (S _{max})	11500 VA	13800 VA	
Rated AC grid voltage (V _{acr})	400 V		
AC voltage range	320...480 V ¹⁾		
Maximum AC output current (I _{ac,max})	16.6 A	20.0 A	
Contributory fault current	19.0 A	22.0 A	
Rated output frequency (f _r)	50 Hz / 60 Hz		
Output frequency range (f _{min} ...f _{max})	47...53 Hz / 57...63 Hz ²⁾		
Nominal power factor and adjustable range	> 0.995, adj. ± 0.9 with P _{acr} =10.0 kW, ± 0.8 with max 11.5 kVA	> 0.995, adj. ± 0.9 with P _{acr} =12.5 kW, ± 0.8 with max 13.8 kVA	
Total current harmonic distortion	< 2%		
AC connection type	Screw terminal block, cable gland M40		
Output protection			
Anti-islanding protection	According to local standard		
Maximum external AC overcurrent protection	25.0 A		
Output overvoltage protection - varistor	3 plus gas arrester		
Operating performance			
Maximum efficiency (η _{max})	97.8%		
Weighted efficiency (EURO/CEC)	97.1% / -	97.2% / -	
Feed in power threshold	30.0 W		
Night consumption	< 1.0 W		

Block diagram of PVI-10.0/12.5-TL-OUTD



Technical data and types

Type code	PVI-10.0-TL-OUTD		PVI-12.5-TL-OUTD
Communication			
Wired local monitoring	PVI-USB-RS232_485 (opt.)		
Remote monitoring	VSN300 Wifi Logger Card (opt.), PVI-AEC-EVO (opt.), VSN700 Data Logger (opt.)		
Wireless local monitoring	VSN300 Wifi Logger Card (opt.)		
User interface	16 characters x 2 lines LCD display		
Environmental			
Ambient temperature range	-25...+60°C (-13...+140°F) with derating above 55°C (131°F)	-25...+60°C (-13...140°F) with derating above 50°C (122°F)	
Relative humidity	0...100% condensing		
Sound pressure level, typical	50 dBA @ 1 m		
Maximum operating altitude without derating	2000 m / 6560 ft		
Physical			
Environmental protection rating	IP 65		
Cooling	Natural		
Dimension (H x W x D)	716 mm x 645 mm x 224 mm / 28.2" x 25.4" x 8.8"		
Weight	< 41.0 kg / 90.4 lbs		
Mounting system	Wall bracket		
Safety			
Isolation level	Transformerless		
Marking	CE (50 Hz only), RCM		
Safety and EMC standard	EN 50178, IEC/EN 62109-1, IEC/EN 62109-2, AS/NZS 3100, AS/NZS 60950.1, EN 61000-6-2, EN 61000-6-3, EN 61000-3-11, EN 61000-3-12		
Grid standard (check your sales channel for availability)	CEI 0-21, CEI 0-16, DIN V VDE V 0126-1-1, VDE-AR-N 4105, G59/3, C10/11, EN 50438 (not for all national appendices), RD 1699, RD 413, RD 661, P.O. 12.3, AS/NZS 4777.2, AS/NZS 4777.3, IEC 61727, IEC 62116, BDEW, MEA, NRS 097-2-1		
Available products variants			
Standard	PVI-10.0-TL-OUTD		PVI-12.5-TL-OUTD
With DC switch	PVI-10.0-TL-OUTD-S		PVI-12.5-TL-OUTD-S
With DC switch and fuse	PVI-10.0-TL-OUTD-FS		PVI-12.5-TL-OUTD-FS

¹⁾ The AC voltage range may vary depending on specific country grid standard


²⁾ The Frequency range may vary depending on specific country grid standard

³⁾ Limited to 10000 W for Belgium and Germany


⁴⁾ Limited to 12500 W for Germany

Remark. Features not specifically listed in the present data sheet are not included in the product

Efficiency curves of PVI-10.0-TL-OUTD



Efficiency curves of PVI-12.5-TL-OUTD



Support and service

ABB supports its customers with dedicated, global service organization in more than 60 countries and strong regional and national technical partner networks providing complete range of life cycle services.

For more information please contact your local ABB representative or visit:

www.abb.com/solarinverters
www.abb.com/solar
www.abb.com

© Copyright 2015 ABB. All rights reserved.
 Specifications subject to change without notice.

